



GENERAL MONITORS
Protection for life.

MODEL TL105

Test Lamp For Flame Detection



Features

- Rechargeable / replaceable battery
- Easy grip handle integral with housing
- Battery charger status indicator
- Explosion proof cast aluminum housing
- Microcontroller

Benefits

- Extended product life
- Easy to use
- Ease of maintenance
- For use in Class I, Divisions 1 & 2 locations
- Monitors all operations

Description

The TL105 is a battery operated, rechargeable test lamp specifically designed to test General Monitors' UV, UV/IR and IR flame detectors. The test lamp provides a high-energy, broadband radiation source that emits sufficient energy in both the ultraviolet and infrared spectra to activate UV and/or IR flame detectors. To simulate a fire, the test lamp automatically flashes at various selectable rates.

The TL105 is designed for use in Class I, Divisions 1 & 2, Groups C and D areas. The test lamp functions on internal nickel-metal hydride batteries which, when fully charged, allows continuous operation for at least 45 minutes. An internal circuit prevents operation when the battery charge is low.

A variety of flashing test patterns, selectable through a rotary switch, allows the test lamp to check the operation of General Monitors flame detectors, including the FL3000/3100 series, the FL4000, Types V and VI detectors. When the specific flashing pattern for a given type of flame detector is appropriately selected, the test lamp triggers the alarm or test mode.

Specifications

Output Spectrum:	Broadband emissions in UV, visible and IR spectra
Charging Time:	3.5 hours max.
Charger Input:	110-240VAC, 50/60 Hz, 1.5A
Charger Output:	24 VDC @ 2.1A
Classification:	Class I, Zone I, T4 (110°C) Ex d IIB + H ₂
Operating Temperature Range:	5°F to +122°F (-15°C to +50°C)
Humidity:	0-90% ±3% RH, non-condensing
Length:	13 inches (330 mm)
Diameter:	5 inches (127 mm)
Weight:	7.9 lbs (3.5 kg)
Warranty:	Two years
Approvals:	CSA, ATEX, CE Marking
Standard Configuration:	TL105-0-2 Includes power supply adapter



MODEL TL100 UV TEST LAMP

The General Monitors TL100 UV Test Lamp is a portable, rechargeable source of ultraviolet radiation, specifically designed for use in testing General Monitors UV flame detectors. It emits a wide band of radiation, which includes the 185 to 260 nanometer region.

To avoid damaging exposure to ultraviolet radiation, the TL100 provides a "Power On" indicator so that direct viewing of the lamp is not necessary. The TL100 is approved by CSA as intrinsically safe for use in Class I, Division 1, Groups C & D.

Features

- Intrinsically safe
- Rugged and lightweight
- Two UV intensity levels
- Power ON indicator (eliminates need to view UV lamp directly)
- Low battery indicator
- Typically two-hour operating time between charges
- Regulated lamp intensity
- 3-position momentary switch (HI / OFF / LO)



Specifications

Operating Temperature:	32°F to 158°F (0°C to 70°C)
Weight:	1 lb (0.45 kg)
Dimensions:	11"L x 2.25" D (279 mm L x 57 mm D)
Operating Time:	2 hours (approximately)
Charging Time:	14 to 16 hours
Charger Input:	120V + 15% 50/60 Hz, 3W nominal
Output:	9 VDC @ 47 mA
Approvals:	CSA, CE Marking
Standard Configuration:	TL100-2 Includes battery charger

Specifications subject to change without notice.

Represented by:

General Monitors Worldwide



www.generalmonitors.com

Lake Forest, CA

26776 Simpatica Circle
Lake Forest, California 92630
Tel: +1-949-581-4464
Fax: +1-949-581-1151
Email: info@generalmonitors.com

Houston, TX

9776 Whithorn Drive
Houston, Texas 77095
Tel: +1-281-855-6000
Fax: +1-281-855-3290
Email: gmlhou@generalmonitors.com

Ireland

Ballybrit Business Park
Galway
Republic of Ireland
Tel: +353-91-751175
Fax: +353-91-751317
Email: info@gmil.ie

Singapore

No. 2 Kallang Pudding Road
#09-16 Mactech Building
Singapore 349307
Tel: +65-6748-3488
Fax: +65-6748-1911
Email: genmon@gmpacifica.com.sg

United Arab Emirates

P.O. Box 61209
Jebel Ali
Dubai
United Arab Emirates
Tel: +971-4-8815751
Fax: +971-4-8817927
Email: gmme@emirates.net.ae

United Kingdom

Heather Close
Lyme Green Business Park
Macclesfield, Cheshire
United Kingdom, SK11 0LR
Tel: +44-1625-619583
Fax: +44-1625-619098
Email: info@generalmonitors.co.uk